





Our H-frame press, 30 ton, can be operated by hand as well as by foot: the handpump is interchangeable to a foot pump. This hydraulic workshop press has a fixed cylinder and the height of the work table is easy to adjust. Thanks to the in-height adjustable work table of this H-frame press, you can easily work with different material / product sizes.

The hand- and foot operated Pro Presses have an integrated manometer and a chrome piston (that returns automatically). Standard supplied with a set of V-blocks for extra support. These manual workshop presses are made in Europe and delivered according to the latest CE standards.

Ask us for an offer below or [contact us directly](#) by telephone or e-mail!

We keep these hand- and foot operated H-frame presses in our stock in the Netherlands, so if you need one fast, let us know! We deliver them over the whole world and within Europe we can deliver these presses within a couple of days.

#### **Technical specifications of the 30 ton HF-2**

- ◆ Pressure force [kN]: 294.3
- ◆ Pressure max. [bar]: 374.6
- ◆ Cylinder stroke [mm]: 160
- ◆ System capacity [dm<sup>3</sup>]: 1,65
- ◆ Movable cylinder: No
- ◆ Working width [mm]: 565
- ◆ Weight [kg]: 165

#### **Diameters**

- ◆ Inside diameter of cylinder [mm]: 115
- ◆
- ◆

Diameter of piston rod [mm]: 40

Diameter of piston head [mm]: 50

### **Features**

- ◆ Hand- and foot operated (the hand pump can be changed into a foot pump without any effort)
- ◆ Fixed cylinder
- ◆ The height of the worktable is easy to adjust
- ◆ Integrated pressure manometer
- ◆ Chromed piston
- ◆ Automatic piston return
- ◆ V-block set