

Our manual hydraulic press (50 ton HF-2) can be operated by hand as well as by foot: the handpump is interchangeable to a foot pump. This workshop press has a movable cylinder and the height of the work table is easy to adjust with a winch. Thanks to the inheight adjustable work table of this hydraulic press, you can easily work with di erent material / product sizes.

The hand- and foot operated Pro Presses have an integrated manometer and a chrome piston (that returns automatically). Standard supplied with a set of V-blocks for extra support. These manual hydraulic presses are made in Europe and delivered according to the latest CE standards.

Ask us for an o er below or contact us directly by telephone or e-mail!

We keep these hand- and foot operated hydraulic presses in our stock in the Netherlands, so if you need one fast, let us know! We deliver them over the whole world and within Europe we can deliver these presses within a couple of days.

Technical specifications of the 50 ton HF-2

- Pressure force [kN]: 490.5
- Pressure max. [bar]: 399.5
- Cylinder stroke [mm]: 160
- System capacity [dm³]: 2.5
- Movable cylinder: yes
- •Working width [mm]: 750
- Weight [kg]: 340

Diameters

- Inside diameter of cylinder [mm]: 140
- Diameter of piston rod [mm]: 50
- Diameter of piston head [mm]: 60

Features

- Hand- and foot operated
- Movable cylinder
- The height of the worktable is easy to adjust by means of a winch
- Integrated pressure manometer
- Chrome piston
- Automatic piston return
- V-block set

Optional

Mandrel set of Ø 5, 10, 14, 18, 24 and 29 mm (with a suitable piston head for the 50 ton HF-2)