



Fully adjustable spray pressure TW1250

TW1250

Spray-extraction machine with a high suction performance for the professional cleaning of large areas. The spray pressure is fully adjustable from 2 to 11 bar.



Technical data:

| iccillical data. | |
|----------------------|---------------------|
| Total power | 1700 W/230 V |
| Vacuum | 250 mbar |
| Fresh water capacity | 35 I |
| Dirty water capacity | 40 l |
| Pump pressure max. | 2-11 bar adjustable |
| Spray pressure | up to 3,6 l/min |
| Airflow capacity | 60 l/sec |
| Vacuum width | 30 cm |
| Cable length | 20 m |
| Weight | 44 kg |
| Measurements I/w/h | 82 / 41 / 84 cm |



| 125.400 | Spray and suction hose HP |
|---------|------------------------------|
| | (high pressure), 4 m |
| 500.863 | Extension cable 20 m |
| 611.000 | Carpet adapter, 4 jet 30 cm, |
| | alu high pressure |
| | |

Special accessories

| 617.000 | Upholstery tool 8 cm, PVC, |
|---------|--------------------------------------|
| | anthracite, with nozzle inside |
| 618.000 | Upholstery tool 9 cm, alu, |
| | with nozzle outside |
| 622.000 | Wall and ceiling tool, 9 cm |
| 638.000 | Hard floor adapter, 37 cm, Ø 38 mm |
| 681.000 | Filling up hose for fresh water, 2 m |



to the tank



Stepless pressure regulation



Maintenance-friendly



Climbing stairs thanks to large wheels



Cleanfix Reinigungssysteme AG Stettenstrasse 15 | 9247 Henau-Uzwil/SG Tel. +41 71 955 47 47 | info@cleanfix.com www.cleanfix.com